



Amerex Corporation

RUGGED

- 5 Year Warranty
- All Metal Valve Construction
- Rust free aluminum cylinders
- Durable High Gloss Polyester Powder Paint
- Temperature Range -22°F to 120°F

USER FRIENDLY

- Meets Many Hospital Medical Equipment Requirements
- Large Loop Stainless Steel Pull Pin
- Model 322NM Independently Tested and Approved for use in MRI Facilities to 11.7 Tesla
- Model 322NM Has Sanitary White Paint Finish (easy to clean)
- Bar Coded and Bi-lingual Labels

OPTION

- USCG Approved with Bracket Listed on UL Label



MODELS
 332 330 331
 320 322



Also available in 50 / 100 lb. wheeled extinguishers and 100 lb. stationary.

Models
320NM 322NM
NONMAGNETIC

MRI SAFE
UP TO
11.7 TESLA



CARBON DIOXIDE is discharged as a white cloud of “snow” which smothers a fire by eliminating oxygen. It is effective for Class B flammable liquids and is electrically non-conductive. Carbon Dioxide is a clean, non-contaminating, odorless gas.

Non-Magnetic model available (Models 320NM and 322NM - Tested to 11.7 Tesla)

AGENT TYPE	CARBON DIOXIDE						
VALVE TYPE	CHROME PLATED BRASS						
DESIGN	HORN				HOSE & HORN		
MODEL NUMBER	320	320NM	322	322NM	330	331	332
UL RATING	2B:C	2B:C	5B:C	5B:C	10B:C	10B:C	10B:C
CAPACITY (LBS.)	2.5	2.5	5	5	10	15	20
SHIPPING WT. (LBS.)	8.9	8.9	14	14	28.25	37.75	50.75
HEIGHT (IN.)	13.25	13.25	17.75	17.75	24	30	30
WIDTH (IN.)	7.25	7.25	8.25	8.25	12	12	13
DEPTH (IN.)	14.38	14.38	5.25	5.25	7	7	8
RANGE (INITIAL- FT)	3 - 8	3 - 8	3-8	3-8	3-8	3-8	3-8
DISCHARGE TIME (SEC.)	9	9	10	10	10	12.5	19
FM APPROVED	NO	NO	YES	YES	YES	YES	YES
INCLUDED BRACKET	WALL	WALL	WALL	NM WALL	WALL	WALL	WALL

Manufactured and Tested to ANSI/UL Standards

**Complies with NFPA 10 Standard
 ISO-9001 / ISO-14001 Certified
 UL LISTED**

CONFORMS TO TEST STANDARDS:

CAN/ULC-S503 - ANSI/UL154 &
 CAN/ULC-S508 - ANSI/UL711

MADE IN U.S.A.